## OF PROCESSED MATERIAL

**DESCRIPTION:** POLYESTER BRAID DRY WAXED

**LYRA 0.8** 

TOL.

±8%

± 5%

± 10%

± 4%

TECHNICAL CHARACTERISTICS
TECHNICAL CHARACTERISTICS

COMPOSITION

BEATS FOR METER

RESISTANCE TO TENSILE

SHRINKING AFTER DRY-CLEA-

NING AND IRONING AT 160°C

SHRINKING TO HUMIDITY

**FASTNESS OF COLOUR** 

**FASTNESS OF COLOUR** 

**FASTNESS OF COLOUR** 

**FASTNESS OF COLOUR** 

TO DRY-CLEANING WITH

TO DOMESTIC WASHING

**CHARACTERISTIC** 

LENGTH OF THREAD ON BOBBIN

BASE OF SUPPORT DIAMETER

SOFTENING POINT

HEIGHT OF BOBBIN

**PERCHLORETHYLENE FASTNESS OF COLOUR** 

METRIC YIELD

**EXTENSIBILITY** 

TO RUBBING

TO WATER

TO LIGHT

**STRESS** 

COUNT

-	TECHNICAL CHARACTERISTICS		
CHARACTERISTIC	REG.	UNIT	Г

ISO 2060

ISO 2062

ISO 2062

ISO 3175

EN 25077

ISO

105-X12

ISO

105-E01

ISO

105-B02

ISO

105-D01

ISO

105-C06

**VALUE** 

100% POLYESTER

288 (12 YARN)

710

3400

15000

18

≤ 3

≤ 3

≥ 3

> 3

≥ 4

≥ 3

≥ 3

240

**VALUE** 

1000

94

99

TFX

N°

M/KG

g

%

%

%

SCALE OF GREYS

SCALE OF GREYS

SCALE OF BLUES

SCALE OF GREYS

SCALE OF GREYS

°C

TERMS OF BOBBINS SUPPLYING

UNIT

m

mm

mm