

**DESCRIPTION:** POLYESTER BRAID WAXED FOR HAND SEWING

**URSA 0.8**
**TECHNICAL CHARACTERISTICS**

CHARACTERISTIC	REG.	UNIT	VALUE	TOL.
COMPOSITION			100% POLYESTER	
COUNT	ISO 2060	TEX	290 (12 YARN)	± 8%
BEATS FOR METER		N°	710	
METRIC YIELD		M/KG	3400	
RESISTANCE TO TENSILE STRESS	ISO 2062	g	15000	± 5%
EXTENSIBILITY	ISO 2062	%	18	± 10%
SHRINKING AFTER DRY-CLEANING AND IRONING AT 160°C	ISO 3175	%	≤ 3	
SHRINKING TO HUMIDITY	EN 25077	%	≤ 3	
FASTNESS OF COLOUR TO RUBBING	ISO 105-X12	SCALE OF GREYS	≥ 3	
FASTNESS OF COLOUR TO WATER	ISO 105-E01	SCALE OF GREYS	≥ 3	
FASTNESS OF COLOUR TO LIGHT	ISO 105-B02	SCALE OF BLUES	≥ 4	
FASTNESS OF COLOUR TO DRY-CLEANING WITH PERCHLORETHYLENE	ISO 105-D01	SCALE OF GREYS	≥ 3	
FASTNESS OF COLOUR TO DOMESTIC WASHING	ISO 105-C06	SCALE OF GREYS	≥ 3	
SOFTENING POINT		°C	240	± 4%

**TERMS OF BOBBINS SUPPLYING**

CHARACTERISTIC	UNIT	VALUE
LENGTH OF THREAD ON BOBBIN	m	700
BASE OF SUPPORT DIAMETER	mm	70-75
HEIGHT OF BOBBIN	mm	107